
Speedy joi	nt		230
A.	Sleeve nut		235
Tube			236

Quick connector

Specification:

Fluid	air ,vacuum(fesible when non-corrosive media)
Operating pressure range Mpa	0~1.1
Ambient temperature Mpa	−10~60°C
hose applicable	PU or nylon hose

How to order:



Û	Series: F:black,W:white
2	Туре
8	Hose outer dia.(unit; mm)
4	Type & size of thread




Outer dia.3	Metric						
Туре	4	6	8	10	12	16	20
Outer dia.(mm)	φ4	φ6	φ8	φ 10	φ 12	φ 16	φ 20

Type & size of thread $\textcircled{4}$			Metric					
turo	M5	M6	M10	M12	M12	M14	M16	M20
type	M5 × 0.8	M6 × 1	M10 × 1	M12 × 1.25	M12 × 1.5	M14 × 1.5	M16 × 1.5	M20 × 1.5

British system cone thread

Туре	01	02	03	04
Size	G1/8	G1/4	G3/8	G1/2







 \Rightarrow **SDPC**[®].



 $\textcircled{SDPC}^{\mathbb{R}}$



 \Rightarrow **SDPC**[®].



SM(outer thread)


	tupo	thread	dim	nension(n	nm)
	type	Т	Ls	Dmex.	Bs
	SM-20	G 1/4"	55.5	¢ 25	φ 7.5
	SM-30	G 3/8"	57.5	¢ 25	φ 7.5
	SM-40	G 1/2"	59.5	¢ 25	φ9

SF(inner thread)

SP(nut)


Ţ	tuno	thread	dim	nension(m	nm)
	type	Т	Ls	Dmex.	Bs
	SF-20	G 1/4"	52.5	¢ 25	φ 7.5
	SF-30	G 3/8"	54.5	¢ 25	φ 7.5
L3	SF-40	G 1/2"	54.5	¢ 25	φ9

SH(Joint type)					
·	type	hose	dimension(mm)		
	type	size⊺	Ls	Dmex.	Bs
	SH-20	5/16" Hose	72.5	ф 25	φ5
	SH-30	3/8" Hose	76.5	φ 25	φ 7.5
	SH-40	1/2" Hose	78.5	^{hex} 26/30	φ9



how to order:






PIM(External thread type)

Image: second		tupo	thread	dimension(mm)		
PM-30 G 3/8" 43 ^{tex} 17/19.6 φ 7.5		type		Lр	^{hex} D	Bp
		PM-20	G 1/4"	41	^{hex} 17/16.2	φ 7.5
PM-40 G 1/2" 46 hex 21/422 \$\phi 7.5		PM-30	G3/8"			
	Lp	PM-40	G 1/2"	46	hex.21/42.2	φ 7.5

PH(Joint type)




PF (inner thread)



Thread	dimension(mm)				
	Lp	hex D	Bp		
G 1/4"	38	^{hex.} 17/16.2	φ 7.5		
G 3/8"	41	^{hex.} 21/24.2	φ 7.5		
G 1/2"	43	hex 26/30	φ 7.5		
	G 1/4" G 3/8"	Lp G 1/4" 38 G 3/8" 41	Lp ^{hex} D G 1/4" 38 ^{hex} 17/162 G 3/8" 41 ^{hex} 21/242		

PP (nut type)






Pipe

Character:

- Good endurance of vibration, corrosion, abrasion and flection.
- Easily use with its kight weight.
- Fits for kinds of joint connector with its high precision.
- Many colors for choice.


How to order:



PU tube

type	length(m/roll)
PU4 × 2.5	200
PU6 × 4	200
PU8 × 5	100
PU8 × 6	100
PU10 × 6.5	100
PU12 × 8	100

How to order:



Length spec:

Color:

2	3	5	7	10	14	20	TTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTT	
2m	3m	5m	7m	10m	14m	20m	(C) SDDD and S	Shine (second s
								Cart
								(((())))
							au -	

Specification:

Fluid	air
Operating pressure range Mpa	0~1.0 Mpa
Ambient temperature Mpa	−15~60°C





С

trans-

В

BU

0